

Instabus Logic Module

Order No.: 0574 00

Instabus Connection device

Order No.: 0597 00

Function

This device is a product of the *instabus* EIB-system and complies with EIBA directives. Detailed technical knowledge obtained in *instabus* training courses is a prerequisite for proper understanding.

Functionality of the devices is depending on the software. Detailed information on loadable software and attainable functionality may be taken from the manufacturer's product database.

Device for the programming of extensive linkages such as locking, release, acknowledgement. Commands from the *instabus* EIB-system are received and processed, the result being sent as a command to the *instabus* EIB.

Alternatively this bus coupler is used as an interface between the *instabus* EIB and application modules such as switch clock, brightness sensor or switch actuator. A bus coupler allows connection of either two switch actuators or any combination of sensors (e.g. switch clock and brightness sensor). Up to four channels may be connected. The combination of sensor and actuators is not possible.

Installation

Caution! The installation and assembly of electrical equipment may be carried out only by a skilled person.

Planning, installation and commissioning of the unit is done by means of EIBA certified software.

Technical Data

Supply <i>instabus</i> EIB:	24 V DC (+6 V/-4 V) via bus coupler
Power drain <i>instabus</i> EIB:	max. 100 mW
connection <i>instabus</i> EIB:	Pressure contact on data bar
Ambient temperature:	-5 °C to +45 °C
Storage temperature:	-25 °C to +55 °C
Type of protection:	IP 20
Build-in width:	18 mm (1 PU)

Acceptance of guarantee

We accept the guarantee in accordance with the corresponding legal provisions.

Please return the unit postage paid to our central service department giving a brief description of the fault:

Gira
Giersiepen GmbH & Co. KG
Service Center
Dahlienstrasse 12
D-42477 Radevormwald



The CE sign is a free trade sign addressed exclusively to the authorities and does not include any warranty of any properties.

Gira
Giersiepen GmbH & Co. KG
Postfach 1220
D-42461 Radevormwald

Telefon: +49 / 21 95 / 602 - 0
Telefax: +49 / 21 95 / 602 - 339
Internet: www.gira.de